#### **Product Technical Sheet**

## **ENlight®**

Thermostatic Electric Shower - Back To Wall

Product Codes	
	I
ENlight® BTW - 9.5kW - White (Black Kit)	GEENLB91
ENlight® BTW - 9.5kW - Grey (Black Kit)	GEENLB93
ENlight® BTW - 9.5kW - Taupe (Black Kit)	GEENLB97

#### Installation

- Inlet connection: 15mm diameter
- Outlet connection: 1/2" BSP male thread

#### Commissioning

• Simple 2 minute commissioning process

#### **End User**

- Tri-Protect® precise thermostatic temperature control
- Feedback panel showing selected temperature and shower duration
- Timing function helping reduce shower time and running costs
- 5-minute Eco Mode to help reduce water usage and costs
- Back to wall space saving kit
- 5 spray shower head with removable spray plate and 1.5m anti-twist hose
- Efficient A energy rating



























## **Product Technical Sheet**

# **ENlight®**

### Thermostatic Electric Shower - Back To Wall

Shower		
T	l =	
Temperature stability	Thermostatic Tri-protect®	
Power ratings	9.5kW (at 240V)	
Finish	White, Grey, Taupe	
Controls	Soft press buttons, Eco mode acts as a start/stop button	
Visual Indicators (LED & OLED display)	Power-on/low pressure indicator & Operation Indicator	
Inlet Connection	15mm male compression	
Water Entry Points	Top, bottom, back (right hand side unit)	
Cable Entry Points	Top, bottom, back (right hand side unit)	
Outlet Connection	½" BSP	
Plumbing System Compatibility	Cold mains only	
Minimum Running Pressure/Flow	1 Bar @ 8 l/min	
Maximum Static Pressure	10 Bar	
Approvals, Complies with	BEAB, CE, UKCA, BSI Kitemark, IP24	
Guarantee	2 years	

















Riser Rail Kit	
Length	530mm (without brackets), 565mm (with brackets)
Material	Stainless Steel
Finish	Matte Black
Hose	1.5m anti-twist double interlocked



Enya - 5 Spray

Matte Black

GAENYSH3





#### **IMPORTANT MAINTENANCE NOTICE**

Replacing specified Triton accessories for this Enlight® unit will aid optimum performance and maintain a valid guarantee