

# Mira React Bath Filler +

Thermostatic Bath Filler  
(Deck Mounted)



SUITABLE FOR ALL SYSTEMS



5 YEAR WARRANTY

Easy to fit and easy to maintain, the thermostatic Mira React Bath Filler+ with integrated valve isolation, is the perfect blend of precision technology and understated style

## Product Information

Description	Colour	Product No.
Mira React Bath Filler +	Chrome	1.1900.026

## Features & Benefits

### Temperature control

Thermostatic temperature stability

### Easy to fit

Standard deck mount, easy fit elbows and integrated supply isolation

### For your customer

Compatible with all systems, even at low pressure

Separate flow and temperature controls

Deck mount elbows allow bath-edge installation

Temperature control has maximum temperature stop for increased safety (with override for a hotter bath)

Mira Cool Shield™ to ensure valve doesn't get hot to touch during use



# Product Specification

## Tech Details

### Temperature and flow control

Temperature control type: Thermostatic

Flow control type: Ceramic

### Installation

Deck mounted easy fit elbows, supports 2nd fix valve installation

Standard 180 mm centers for the replacements of existing Bath Shower Mixers

Inlet connections: 3/4" BSP male under bath connections to pipework;  
3/4" BSP connection to mixer shower

Integrated bi-directional 1/4 turn full-bore ball valve isolators:

- Saves time and resources when conducting in service cold failure testing to comply with TMV 2
- Saves time and resources for in service maintenance (i.e cleaning filters and not having to remove bath panel)
- No specialist tools required: Easily isolate the water supply using a flat head screwdriver or hex key

### Supply Conditions (hot and cold)

Cold water range: 1°C to 25°C

Hot water range: Min 55°C; 60°C - 65°C (recommended)

Minimum maintained pressure (gas water heater) :  
1 bar (10 metre head)

Minimum maintained pressure (gravity system) : 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

## Performance

Flow rate (at bath outlet): 15 l/min at 0.6 bar

Temperature stability:  $\pm 2^{\circ}\text{C}$

## Safety Features

Automatic shut down: Shut down within 2 seconds to comply with TMV2 requirements

Factory set to safe max temp: 39°C at maximum temperature stop, 46°C using override\*

Adjustable maximum temperature for on-site conditions

## Approvals

KIWA UK approved product

WRAS approved (Water Regulations Advisory Scheme)

TMV2 approved product



\*Preset to a safe temperature under ideal conditions at the factory, appropriate for most systems. Site conditions and personal preference may make it necessary to reset this temperature.

## Dimensions

