

Mira React Bathfiller Non-thermostatic

Deck Mounted



Easy to fit, with a universal design. Mira React Bathfiller can work across any bathroom providing enhanced performance and understated style.



Product Information

Description	Colour	Product No.
Mira React Bathfiller	Chrome	2.1977.003

Features & Benefits

Easy to fit

Easy to fit

Standard 180mm centres ensure a quick and simple replacement to existing products

For your customer

The robust brass construction ensures durability

The simple, easy to use lever handle with hot and cold indicators ensure that it is easy to use

Style-matched to the Mira React showering range

Product Specification

Tech Details

Temperature and flow control

Temperature control type: Non- Thermostatic

Flow control type: Ceramic

Installation

Standard 180mm centres ensure a quick and simple replacement to existing products

Inlet connections: 3/4" BSP male under bath connections to pipework;
3/4" BSP Connection to Mixer Shower

Performance

Flow rate: 36 L/min at 0.5 bar

Supply Conditions (hot and cold)

Cold water range: 1°C to 25°C

Hot water range: Min 55°C; 60°C - 65°C (recommended)

Minimum Dynamic Pressure: 0.2 bar (2 metre head)

Recommended Dynamic Pressure: 1.0 bar (10 metre head) +

Maximum Dynamic Pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

Dimensions

